

																
				bar	psi	kg	lbs	mm	inch	mm	inch				mm	x/32"
Black Sidewall																
18"	235 / 40 ZR 18	92 W	8.5	3.5	50	630	1389	241	9.5	645	25.4	8.5	10.7	302	1967	8.0 - 9.5
	225 / 40 ZR 18	88 W	8.0	3.5	50	560	1235	230	9.1	637	25.1	8.5	10.7	299	1943	7.5 - 9.0
	225 / 45 ZR 18	91 W	7.5	3.0	44	615	1356	225	8.9	659	25.9	8.5	10.7	307	2010	7.0 - 8.5
17"	255 / 40 R 17	94 H	9.0	3.0	44	670	1477	260	10.2	636	25.0	8.0	10.1	296	1940	8.5 - 10.0
	235 / 40 R 17	90 H	8.5	3.0	44	600	1323	241	9.5	620	24.4	8.3	10.5	289	1891	8.0 - 9.5
	215 / 40 R 17	83 H	7.5	3.0	44	487	1074	218	8.6	604	23.8	8.3	10.5	283	1842	7.0 - 8.5
	205 / 40 R 17	80 H	7.5	3.0	44	450	992	212	8.3	596	23.5	8.3	10.5	280	1818	7.0 - 8.0
	255 / 45 R 17	98 H	8.5	3.0	44	750	1653	255	10.0	662	26.1	8.5	10.7	306	2019	8.0 - 9.5
	245 / 45 R 17	95 H	8.0	3.0	44	690	1521	243	9.6	652	25.7	8.5	10.7	302	1989	7.5 - 9.0
	235 / 45 ZR 17	94 W	8.0	3.0	44	650	1433	236	9.3	644	25.4	8.5	10.7	299	1964	7.5 - 9.0
	235 / 45 R 17	94 H	8.0	3.0	44	670	1477	236	9.3	644	25.4	8.5	10.7	299	1964	7.5 - 9.0
	225 / 45 R 17	91 H	7.5	3.0	44	615	1356	225	8.9	634	25.0	8.5	10.7	295	1934	7.0 - 8.5
	215 / 45 R 17	87 H	7.0	3.0	44	545	1201	213	8.4	626	24.6	8.5	10.7	292	1909	7.0 - 8.0
	215 / 45 ZR 17	87 W	7.0	3.0	44	545	1201	213	8.4	626	24.6	8.5	10.7	292	1909	7.0 - 8.0
	225 / 50 ZR 17	94 W	7.0	3.0	44	670	1477	233	9.2	658	25.9	8.5	10.7	304	2007	6.0 - 8.0
	215 / 50 ZR 17	91 W	7.0	3.0	44	615	1356	226	8.9	648	25.5	8.5	10.7	300	1976	6.0 - 7.5
	215 / 50 R 17	91 H	7.0	3.0	44	615	1356	226	8.9	648	25.5	8.5	10.7	300	1976	6.0 - 7.5
255 / 55 R 17	102 H	8.0	3.0	44	850	1874	233	9.2	680	26.8	8.5	10.7	313	2074	7.0 - 9.0	
16"	205 / 40 R 16 RF	83 H	7.5	3.0	44	487	1074	214	8.4	570	22.4	8.1	10.2	267	1739	7.0 - 8.0
	205 / 45 ZR 16		7.0	3.0	44	487	1074	206	8.1	590	23.2	8.3	10.5	275	1800	6.5 - 7.5
	245 / 50 R 16	97 H	7.5	3.0	44	730	1609	253	10.0	652	25.7	8.5	10.7	299	1989	7.0 - 8.5
	225 / 50 R 16	92 H	7.0	3.0	44	630	1389	233	9.2	632	24.9	8.5	10.7	291	1928	6.0 - 8.0
	225 / 50 R 16	92 V	7.0	3.0	44	630	1389	233	9.2	632	24.9	8.5	10.7	291	1928	6.0 - 8.0
	205 / 50 ZR 16		6.5	3.0	44	530	1168	214	8.4	612	24.1	8.5	10.7	283	1867	5.5 - 7.5
	195 / 50 R 16	84 H	6.0	3.0	44	500	1102	201	7.9	602	23.7	8.3	10.5	279	1836	5.5 - 7.0
	215 / 55 R 16	93 H	7.0	3.0	44	650	1433	226	8.9	642	25.3	8.5	10.7	295	1958	6.0 - 7.5
	205 / 55 R 16	91 V	6.5	3.0	44	615	1356	214	8.4	632	24.9	8.5	10.7	291	1928	5.5 - 7.5
15"	225 / 50 R 15	91 H	7.0	3.0	44	615	1356	233	9.2	607	23.9	8.5	10.7	279	1851	6.0 - 8.0
	215 / 50 R 15	88 H	7.0	3.0	44	560	1235	226	8.9	597	23.5	8.5	10.7	275	1821	6.0 - 7.5
	205 / 50 R 15	86 H	6.5	3.0	44	530	1168	214	8.4	587	23.1	8.3	10.5	271	1790	5.5 - 7.5
	195 / 50 R 15	82 V	6.0	3.0	44	475	1047	201	7.9	577	22.7	8.1	10.2	267	1760	5.5 - 7.0
	195 / 50 R 15	82 H	6.0	3.0	44	475	1047	201	7.9	577	22.7	8.1	10.2	267	1760	5.5 - 7.0
	205 / 55 R 15	88 V	6.5	3.0	44	560	1235	214	8.4	607	23.9	8.5	10.7	279	1851	5.5 - 7.5
	195 / 55 R 15	85 V	6.0	3.0	44	515	1135	201	7.9	595	23.4	8.1	10.2	274	1815	5.5 - 7.0
	205 / 60 R 15	91 H	6.0	2.5	36	620	1367	209	8.2	627	24.7	8.5	10.7	286	1912	5.5 - 7.5
	195 / 60 R 15	88 H	6.0	2.5	36	565	1246	201	7.9	615	24.2	8.0	10.1	282	1876	5.5 - 7.0
	195 / 65 R 15	91 H	6.0	2.5	36	615	1356	201	7.9	635	25.0	8.0	10.1	290	1937	5.5 - 7.0
14"	195 / 60 R 14	86 H	6.0	2.5	36	550	1213	201	7.9	590	23.2	8.0	10.1	269	1800	5.5 - 7.0
	185 / 60 R 14	82 H	5.5	2.5	36	475	1047	189	7.4	578	22.8	8.0	10.1	265	1763	5.0 - 6.5
	185 / 65 R 14	86 H	5.5	2.5	36	535	1179	189	7.4	596	23.5	8.0	10.1	272	1818	5.0 - 6.5
13"	185 / 60 R 13	80 H	5.5	2.5	36	475	1047	189	7.4	552	21.7	8.0	10.1	252	1684	5.0 - 6.5

* RF: Reinforced

UTQGS

Series	Speed	Treadwear	Traction	Temperature
60 ~ 65	H	340	A	A
40 ~ 55	H, V	320	AA	A
35 ~ 55	W, ZR	260	AA	A
195 / 50 R 16	H	320	A	A